Seating Component

MECHANISM #81


3

Type

- >>> Mechanism for executive seating, front pivot with synchro back/seat angle adjustment.
- >> Heavy-duty aluminum alloy casting.

Functions

- >> 360° swivel on column axis.
- A >> Height adjustable (gas cylinder).
 - >>> Synchro tilt of seat from -2° to 11° (front pivot) and back from 85° to 105°.
- B >> Adjustable tilt tension.
- C >>> Tilt lock in 5 positions.
 - >>> Compatible with the adjustable back height (option R).



Adjustment Procedure

- "Using the A lever for seat height adjustment, position the chair to feel slightly elevated. Then activate the lever again to lower the chair position until your legs form a 90 ° angle at the knee height.
- >> Using the C lever for tilt adjustment, set the desired synchronized seat/back angle and lock it. A 3° rearward angle seat position is recommended.
- \red{blue} If you feel that the chair tilts backwards too easily, turn the $\emph{\textbf{B}}$ knob clockwise until there is a slight resistance to movement. If the chair tilt is too tight, turn the $\emph{\textbf{B}}$ knob counterclockwise until there is a slight resistance to movement.
- >> Position yourself next to your work surface and adjust the armrests so that your arms are closest to your body, forming an angle of 90° at elbow height.
- "If your work surface is not the right height for you, please check if adjustment is possible. If you are positioned too low when using the surface and you must increase your chair height, you will probably need a footrest to keep the recommended 90° leg angle.



Telephone: (450) 378-0189 1 800 363-3040 Fax: (450) 378-9712

artopex.com